

Ubiflex B2



Malleable and safe to use as a LEAD-FREE flashing system

The Ubiflex B2 system is conveniently available from the nationwide build shop limited



Ubiflex B2 comes in rolls available in Grey (as shown) or Black finish



Malleable and waterproof



Flashing below window – Black finish

- Applications:
SOAKERS, VALLEY GUTTERS, COVER, WINDOW, DOOR, STEP, ROOFLIGHT & CONSERVATORY FLASHINGS
- Lightweight- heaviest roll (0.4m x 12m) only weighs 10.6.kg
- Malleable – resists work hardening
- Temperature resistant – minus 20°C to plus 90°C
- Ubiflex is a thermal insulator – can be used without cold bridging
- Easy to position and fix – workable in both directions
- Quick to install – resistant to elongation and compression
- Environmentally friendly – the product is recyclable
- Non-toxic – safe to handle
- 15 year warranty from Ubbink
- Service life expectancy – excess of 20 years
- Available in Grey or Black.
- Mark and stain resistant surface
- Compatible with all other building materials
- Materials used to manufacture Ubiflex have no resale value as scrap so installed product is less likely to be stolen

The product is fully malleable, can be worked in both directions and is self sealing if punctured. Ubiflex B2 is 85% lighter than lead giving handling, structural and health and safety advantages.

Easily cut with a craft-knife or snips, Ubiflex B2 is easily formed to the required profile, once bent it will not spring back. Installers have found the Ubiflex system is up to 50% quicker to install than lead.

Please note Ubiflex B2 is not suitable to form sharp corners, damp proof courses and cavity trays in masonry walls. Specify Ubiflex B3 for these applications – Refer separate Ubiflex B3 nbs Data Sheets.



Chimney flashing – Grey finish



Chimney flashing –Black finish