

flexim® GF is a non-mastic, permanent, water resistant Gap Filler that stays flexible

Quantity repair



FLEXIM® GF Gap Filling adhesive mortar can be used for new construction or renovating older structures, to fill and seal gaps in brickwork, stonework and around metal and wood frames. It can also successfully seal gaps in concrete, structures and roof tiles including slate. FLEXIM GF is instantly waterproof. Being lightweight and pliable, FLEXIM GF will retain its shape and will not crack, break or slump like conventional cement based mortars or dry out like most mastic fillers.

Please note, FLEXIM GF cannot be used to reinstate the structural strength of a weight bearing component.

◀ Although safe to handle, to keep hands clean protective plastic gloves are included with each block of FLEXIM GF

Testing and certification

FLEXIM's incredible bonding strength and resistance against the elements has been proven in several tests, performed by highly recognised test institutes in Europe and the US. Adhesion and elasticity tests, which included intensive weathering trials where conducted.

FLEXIM successfully passed the US Metro-Dade PA 100-95 protocol a wind driven rain test with simulated 178 km/h (110 MPH) winds! In the report (TNO Holland) it has been found, that the tensile strength of FLEXIM is 20.000 N/m². This complies with NEN 6707/Bb.



Miami Dade Approved
Report Number 00-0809.05



SBCCI Approved
Report Number 9934

Suitable for most climatic conditions experienced throughout the world



FLEXIM Headquarters

FLEXIM is a reliable solution in most climate zones. That is why FLEXIM has been successful installed in buildings in temperate countries with their cold winters and warm summers. The product is also eminently suitable for tropical and sub-tropical climates where strong sunlight and high humidity is usual.

Schedule for quotation request from the [nationwide build shop](#)

PLEASE SCROLL DOWN OR CLICK THE PAGES ICON (TAB) ON THE LEFT TO READ THE NBS FLEXIM[®] GF DATA SHEETS BEFORE COMPLETING THIS FORM.

To print this form, click **File, Print**, then check **Current page** and click **OK**.



Block size = 480mm x 100mm x 40mm.
Protective plastic cloes included with every block

Please complete the printed form, notating your requirement.

IF YOU WISH TO FORWARD YOUR REQUEST FOR A QUOTATION VIA EMAIL [CLICK HERE](#). COMPLETE YOU'RE CONTACT DETAILS AND IN THE Comments BOX, SIMPLY TYPE IN YOUR REQUIREMENT, THEN CLICK THE Submit BUTTON.

PLEASE ENSURE YOU CALCULATE FOR ALL THE FLEXIM GF REQUIRED FOR THE JOB. WE WILL PROVIDE YOU WITH A FIRM QUOTATION INCLUDING THE DELIVERY CHARGE VIA FOLLOW-UP EMAIL.

IF YOU DECIDE TO ACCEPT OUR QUOTATION PLEASE REPLY VIA EMAIL. WE WILL THEN TELEPHONE YOU FOR YOUR CREDIT CARD DETAILS.

Technical support for this product is available. Please click [contact us](#) on the nbs tool bar, complete your contact details and query. Please note, FLEXIM GF cannot be used to reinstate the structural strength of a weight bearing component.

PACKS OF FLEXIM GF REQUIRED					
Colour required	Tick	Price per block EXCLUDING VAT	Number of blocks required*	Standard carriage/packing charge to one address EXCLUDING VAT	Calculate TOTAL ORDER VALUE
Grey	<input type="checkbox"/>	£		PLEASE NOTE, THE DELIVERY CHARGES GIVEN IN THE NBS SHOP FOR THIS PRODUCT ARE BASED UPON SUPPLYING ONE COLOUR PER DELIVERY. IF MORE THAN ONE COLOUR IS ORDERED PER DELIVERY PLEASE PHONE NBS FOR A SPECIAL DELIVERY CHARGE.	£
Black	<input type="checkbox"/>	£			
Dark Brown	<input type="checkbox"/>	£			
Terracotta	<input type="checkbox"/>	£			
*PLEASE NOTE, WHERE 11 OR MORE BLOCKS ARE ORDERED PHONE OR FAX THIS FORM FOR A SPECIAL DELIVERY CHARGE.					

Delivery conditions apply – Click [conditions](#) on the nbs tool bar then scroll to [Delivery](#)

Your contact details and delivery address

First name:		Last name:		Date: / /	
Your address:			Delivery address: If different		
Post Code:			Post Code:		
Your e-mail:			Please state if there is restricted access to the Delivery address		
Contact telephone:					
OFFICE USE CUSTOMER CREDIT CARD COMPANY : (MasterCard, Visa etc) CREDIT CARD NUMBER: THREE DIGIT SECURITY NUMBER: (Last three numbers usually found on the signature strip) VALID FROM DATE: EXPIRY DATE:					