

Ubiflex

Malleable and safe to use as a LEAD-FREE flashing system



The Ubiflex system is conveniently available from www.nbs-home.co.uk



Ubiflex flashing comes in rolls available in Grey (as shown) Black or Terracotta finish. Terracotta is only available via special quotation.


- Applications:
SHARP CORNERS, VALLEY GUTTERS, COVERS, STEP, ROOFLIGHTS, DPC & CAVITY TRAYS IN MASONRY WALLS, SOAKERS, WINDOW, DOOR, STEP, ROOFLIGHT & CONSERVATORY FLASHINGS.
- Lightweight- heaviest roll (1m x 6m) only weighs 24.0kg
- Malleable – resists work hardening
- Temperature resistant – minus 20°C to plus 90°C
- Ubiflex is a thermal insulator – can be used without cold bridging
- Easy to position and fix – workable in both directions
- Quick to install – resistant to elongation and compression
- Environmentally friendly – the product is recyclable
- Non-toxic – safe to handle
- 25 year warranty from Ubbink
- Service life expectancy – excess of 30 years
- Available in Grey or Black. Terracotta in large orders.
- Mark and stain resistant surface
- Compatible with all other building materials
- Materials used to manufacture Ubiflex have no resale value as scrap so installed product is less likely to be stolen
- **BBA Certified - Certificate No 08/4577**

Ubiflex is fully malleable, can be worked in both directions and is self sealing if punctured. Ubiflex is 80% lighter than lead giving handling, structural and health and safety advantages.

Easily cut with a craft-knife or snips, Ubiflex non-lead flashing is easily formed to the required profile, once bent it will not spring back. Installers have found the Ubiflex system is up to 50% quicker to install than lead.



A digital copy of the BBA Certificate for the Ubiflex System is available from the nationwide build shop.



Malleable and waterproof – the top surface has a granular finish



Chimney flashing – Grey finish



Chimney flashing –Black finish

nationwide
build
shop